

## “ASHWINI” MOBILE CONCRETE PLACER - SERIES



### MOBILE CONCRETE PLACER...

The use of Long Reach Mobile Concrete Placer is that, it allows you to place mass concrete in very short amount of time, even from great heights, and with accuracy. Another key advantage is being Self Propelled it allows you to maneuver around construction site to pour concrete in areas that are inaccessible.

### MOBILE CONCRETE PLACER VARIANT IN LR SERIES:

“ASHWINI” MOBILE CONCRETE PLACER MCP-56

“ASHWINI” MOBILE CONCRETE PLACER MCP-56/650

“ASHWINI” MOBILE CONCRETE PLACER MCP-66

## TECHNICAL FOR “ASHWINI” MOBILE CONCRETE PLACER LONG REACH SERIES

MODEL	MCP-56	MCP-56/650	MCP-66
DISCRIPTION			
Aggregate Mix	Up to 40 mm	Up to 80 mm	Up to 80 mm
Total Length of Conveyor	17 Meters	17 Meters	20.7 Meters
Clear Reach (Rest Position)	9 Meters	9 Meters	10.3 Meters
Clear Reach (Elevated Position)	8 Meters	8.2 Meters	10 Meters
Concrete Placing height	8.5 Meters	8.5 Meters	10 Meters
Concreting Capacity	25-30 Cum/Hr	45-50 Cum/Hr	55-60 Cum/Hr
Belt Width	400 MM (Plain Belt)	650 MM (Plain Belt)	650 MM (Plain Belt)
Belt Drive	Hydraulic	Hydraulic	Hydraulic
Traction Drive	Front - Hydraulic Drive Rear Idler	Front - Hydraulic Drive Rear Idler	Front - Hydraulic Drive Rear Idler
Prime Mover	26 HP Air Cooled Diesel Engine	26 HP Air Cooled Diesel Engine	Air Cooled Diesel Engine
Tyre	3 Nos.	3 Nos.	3 Nos.
Hydraulic Tank	80 Litres	80 Litres	80 Litres
Fuel Tank	25 Ltr	25 Ltr	25 Ltr
Charging Hopper	0.25 Cum	0.25 Cum	0.25 Cum
Control Panel	Engine Panel & Hydraulic Operation Lever	Engine Panel & Hydraulic Operation Lever	Engine Panel & Hydraulic Operation Lever
Painting	As per Manufacturer Standards	As per Manufacturer Standards	As per Manufacturer Standards

Specifications are subject to change without prior notice due to Modification, Alteration or Custom Engineering